

**NEPTUN  
FREEZERSPACER**

World-wide since 1984

- + Highly efficient (documented)
  - + Suitable also for transport
  - + Sturdy and reusable – again and again
  - + Easy to clean and nest
- = Economical, Efficient and Convenient**


**NFS-II**

Due to its unique design ensuring maximum air penetration, a long life span and easy handling, Neptun Freezerspacers are used worldwide by leading enterprises since 1984

The unique design of the Neptun NFS-II spacer ensures maximum air penetration in freezing and tempering situations. Due to the robust structure in High-Density Polyethylene, the spacer withstands temperatures between -40° and +60°C and is resistant to most acids and chemicals, thereby ensuring a long lifespan even in the toughest working environments. The open profile of the NFS II spacer makes it easy to clean and nests well when not in use.

**Technical specs.**

Item No.	Length mm/inch	Width mm/inch	Height mm/inch	Nesting Height	Weight/pcs Gr/Lbs	Material	Max-Load Kg/Lbs	Pcs/pallet	M <sup>3</sup> incl. pallet	KG/Lbs incl. pallet
40.312.05	1200/47"	1000/40"	50/2"	30/1,2"	3360/7,4	HDPE	2000/4400	80	2,9	280/617
40.310.05	1200/47"	800/32"	50/2"	30/1,2"	2720/6	HDPE	2000/4400	80	2,3	230/507

Standard colours; Black – other colours can be supplied on request

- Designed for temperature sensitive applications
- Air circulates rapidly through the cavities of the spacer ensuring a faster and efficient freezing of the whole pallet load.
- Improved support and rigidity makes NFS II usable also when used in transportation
- Maximum air penetration in Freezing and Tempering operations
- Effective at temperatures range between -40° below to plus +60°
- Open profile design allows for easy cleaning
- Nestable for space saving
- 100% recyclable
- High density polyethylene
- For indirect food contact – (For direct food contact can be manufactured on request)

**Shipping information**

Pallets / pcs	Export Trailer (13,62x2,46x2,7)	20ft container (5,9x2,35x2,39)	40ft container (12,03x2,35x2,39)	40 ft HQ container (12,03x2,35x2,69)
1200x800	33 / 2244	11 / 748	25 / 1700	25 / 1975
1200x1000	26 / 1768	9 / 612	22 / 1496	22 / 1738